

## Environmental Protection Agency

§ 428.50

### § 428.42 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.

Except as provided in §§ 125.30 through 125.32, any existing point source subject to this subpart shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available (BPT):

| Effluent characteristic                | Effluent limitations  |   |
|--|-----------------------|---|
|  | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kkg of product)       |                       |   |
| COD .....                              | 10.27                 | 6.85  |
| BOD <sub>5</sub> .....                 | 0.51                  | .34   |
| TSS .....                              | 0.82                  | .55   |
| Oil and grease .....                   | 0.21                  | .14   |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )  |
| English units (lb/1,000 lb of product) |                       |   |
| COD .....                              | 10.27                 | 6.85  |
| BOD <sub>5</sub> .....                 | 0.51                  | .34   |
| TSS .....                              | 0.82                  | .55   |
| Oil and grease .....                   | 0.21                  | .14   |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )  |

<sup>1</sup> Within the range 6.0 to 9.0.

[39 FR 6662, Feb. 21, 1974, as amended at 60 FR 33963, June 29, 1995]

### § 428.43 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

The following limitations establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a point source subject to the provisions of this subpart after application of the best available technology economically achievable:

| Effluent characteristic                | Effluent limitations  |   |
|--|-----------------------|---|
|  | Maximum for any 1 day | Average of daily values for 30 consecutive days shall not exceed— |
| Metric units (kg/kkg of product)       |                       |   |
| COD .....                              | 2.66                  | 1.78  |
| BOD <sub>5</sub> .....                 | 0.11                  | .07   |
| TSS .....                              | 0.21                  | .14   |
| Oil and grease .....                   | 0.11                  | .07   |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )  |
| English units (lb/1,000 lb of product) |                       |   |
| COD .....                              | 2.66                  | 1.78  |
| BOD <sub>5</sub> .....                 | 0.11                  | .07   |
| TSS .....                              | 0.21                  | .14   |
| Oil and grease .....                   | 0.11                  | .07   |
| pH .....                               | ( <sup>1</sup> )      | ( <sup>1</sup> )  |

<sup>1</sup> Within the range 6.0 to 9.0.

### § 428.44 [Reserved]

### § 428.45 Standards of performance for new sources.

The following standards of performance establish the quantity or quality of pollutants or pollutant properties, controlled by this section, which may be discharged by a new point source subject to the provisions of this subpart: The limitations shall be as specified for § 428.42.

### § 428.46 Pretreatment standards for new sources.

Any new source subject to this subpart that introduces process wastewater pollutants into a publicly owned treatment works must comply with 40 CFR part 403.

[60 FR 33963, June 29, 1995]

## Subpart E—Small-Sized General Molded, Extruded, and Fabricated Rubber Plants Subcategory

SOURCE: 40 FR 2336, Jan. 10, 1975, unless otherwise noted.

### § 428.50 Applicability; description of the small-sized general molded, extruded, and fabricated rubber plants subcategory.

The following provisions of this subpart are applicable to process waste water discharges resulting from the production of molded, extruded, and